

Appln. No. 09/599,036

Docket No. 22-0134

AMENDMENTS TO THE CLAIMS

1 (Currently Amended): A method for providing a variable beam hop cycle beam laydown, the method comprising:

transmitting first downlink beam energy for first cells according to a first beam hop cycle;

transmitting second downlink beam energy for second cells according to a second beam hop cycle different from than the first beam hop cycle; and

transmitting transition downlink beam energy for transition cells according to a transition beam hop cycle for transitioning between the first beam hop cycle and the second beam hop cycle;

wherein each beam hop cycle defines how the downlink energy of one beam is time-shared between at least two cells.

2 (Presently Amended): The method of claim 1, wherein transmitting first downlink beam energy comprises transmitting downlink beam energy for a first beam-hopped ~~hop~~ pair of cells, wherein transmitting second downlink beam energy comprises transmitting downlink beam energy for a second beam-hopped ~~hop~~ pair of cells, and wherein transmitting transition downlink beam energy comprises transmitting downlink beam energy for a transition beam-hopped ~~hop~~ pair of cells.

3 (Original): The method of claim 1, wherein transmitting transition downlink beam energy comprises transmitting power gated downlink frames.

4 (Original): The method of claim 1, wherein each transmitting step comprises transmitting at at least a first frequency and first polarization.

Appln. No. 09/599,036

Docket No. 22-0134

5 (Currently Amended): The method of claim 1, wherein transmitting second downlink energy comprises transmitting second downlink beam energy according to a second beam hop cycle that provides additional bandwidth to meet bandwidth needed for one of the second cells.

6 (Currently Amended): The method of claim 1, further comprising the step of reading frame headers that define the first beam hop cycle, second beam hop cycle, and transition beam hop cycle.

B1
7 (Currently Amended): A variable beam hop cycle beam laydown comprising:
first cells supported by a first beam hop cycle;
second cells supported by a second beam hop cycle different from ~~than~~ the first beam hop cycle; and
transition cells supported by a transition beam hop cycle for transitioning between the first beam hop cycle and the second beam hop cycle;
wherein each beam hop cycle defines how the downlink energy of one beam is time-shared between at least two cells.

8 (Currently Amended): The laydown of claim 7, wherein the first cells comprise a first beam-hopped ~~hop~~ pair of cells, the second cells comprise a second beam-hopped ~~hop~~ pair of cells, and the transition cells comprise a third beam-hopped ~~hop~~ pair of cells.

9 (Currently Amended): The laydown of claim 8, wherein the first beam hop cycle is a 50-50 beam hop cycle.

Appln. No. 09/599,036

Docket No. 22-0134

10 (Currently Amended): The laydown of claim 9, wherein the second beam hop cycle is a 75-25 beam hop cycle and wherein the transition beam hop cycle is a 50-25 beam hop cycle.

11 (Currently Amended): The laydown of claim 10, wherein the 50-25 beam hop cycle directs ~~comprises~~ downlink beam energy to ~~in~~ a first transition cell 50 percent of a time period, downlink beam energy to ~~in~~ a second transition cell 25 percent of the time period, and a power gated downlink beam 25 percent of the time period.

12 (Cancelled)

21
13 (Currently Amended): The laydown of claim 7, wherein the first, second, and transition beam hop cycles control ~~comprise~~ downlink beam energy of at least a first frequency and polarization.

14 (Currently Amended): The laydown of claim 7, wherein the first cells are adjacent cells, the second cells are adjacent cells, and the transition cells are adjacent cells.

15 (Currently Amended): The laydown of claim 7, wherein the first cells are non-adjacent cells, the second cells are non-adjacent cells, and the transition cells are non-adjacent cells.

16 (Original): The laydown of claim 7, wherein at least one of the first, second, and transition cells are adjacent cells.

17 (Currently Amended): Apparatus for generating a variable hop cycle beam laydown, the apparatus comprising:

a waveform generator producing a first downlink beam, second downlink beam, and a transition downlink beam;

Appln. No. 09/599,036

Docket No. 22-0134

at least one switch directing the first downlink beam between first feed paths to first cells, directing the second downlink beam between second feed paths to second cells, and directing the transition downlink beam between third feed paths to transition cells;

at least one feed path selection input coupled to the at least one switch; and
a memory for storing downlink beam type definitions that direct the feed path selection input to control the switch according to a first beam hop cycle, a second beam hop cycle different from than the first beam hop cycle, and a transition beam hop cycle;
wherein each beam hop cycle defines how one downlink beam is time-shared between at least two cells.

18 (Original): The apparatus of claim 17, further comprising a power gating circuit coupled to the waveform generator for gating power in the transition downlink beam.

19 (Original): The apparatus of claim 18, wherein the first, second, and transition downlink beams comprise frames with a header field and a payload field.

20 (Currently Amended): The apparatus of claim 17, wherein the first beam hop cycle directs additional bandwidth to one of the first cells to meet bandwidth need.

21 (Currently Amended): The apparatus of claim 20, wherein the first beam hop cycle is a 75-25 beam hop cycle.

22 (Currently Amended): The apparatus of claim 21, wherein the second beam hop cycle is a 50-50 beam hop cycle and wherein the transition beam hop cycle is a 75-25 beam hop cycle.

23 (Cancelled)

Appln. No. 09/599,036

Docket No. 22-0134

24 (Original): The apparatus of claim 17, wherein at least one of the first cells, second cells, and transition cells are adjacent.

25 (Original): The apparatus of claim 17, wherein at least one of the first cells, second cells, and transition cells are non-adjacent.

26 (Previously Submitted): A variable hop cycle beam laydown comprising:
first cells supported by a first hop cycle;
second cells supported by a second hop cycle different than the first hop cycle;
and

transition cells supported by a transition hop cycle for transitioning between the first hop cycle and the second hop cycle,

wherein said transition hop cycle comprises downlink beam energy in a first transition cell a first percent of a time period, downlink beam energy in a second transition cell a second percent of the time period, and a power gated downlink beam for a remaining percent of the time period.

27 (Previously Submitted): Apparatus for generating a variable hop cycle beam laydown, the apparatus comprising:

a waveform generator producing a first downlink beam, second downlink beam, and a transition downlink beam;

at least one switch directing the first downlink beam between first feed paths to first cells, directing the second downlink beam between second feed paths to second cells, and directing the transition downlink beam between third feed paths to transition cells;

at least one feed path selection input coupled to the at least one switch;

Appln. No. 09/599,036

Docket No. 22-0134

a memory for storing downlink beam type definitions that direct the feed path selection input to control the switch according to a first hop cycle, a second hop cycle different than the first hop cycle, and a transition hop cycle,

31 wherein the transition hop cycle specifies transmission of downlink beam energy in a first transition cell a first percent of a time period, specifies downlink beam energy in a second transition cell a second percent of the time period, and specifies a power gated downlink transition beam a remaining percent of the time period; and

a power gating circuit coupled to the waveform generator for gating power in the transition downlink beam.
